

ELECTRIC WASHER - LEV1500

| Category | Characteristics | Dimensions (2 wheels) | Dimensions (4 wheels) |
|----------------------------------|--|---|-----------------------|
| Chassis | Maximum travel speed (km/h) | 25 km/h | |
| | Hydroelectric power steering | 2 guiding wheels | 4 guiding wheels |
| | Front and rear suspension | Suspensions with blades with shock absorbers | |
| | Front brake | Disk | |
| | Rear break | Drum | |
| Pneumatics | Cut front / back | 195R14C 106/104 R | |
| Dimensions / Weight / Capacities | Length (mm) | 4 555 mm | |
| | Width (mm) (Without outside mirrors) | 1 390 mm | |
| | Height (mm) (without air conditioning) | 2 112 mm (+ 83 mm with air conditioning) | |
| | GVWR (kg) (without a driver) | 4 140 kg | 4 480 kg |
| | Pure weight (kg) | 2 680 kg | 2 720 kg |
| | Wheel base (mm) | 2 240 mm | |
| | Ride height (mm) | 150 mm | |
| | Turning radius between pavements | 3 750 mm | 3 000 mm |
| | Turning radius between walls (mm) | 4 500 mm | 3 600 mm |
| | Crossing of slope (%) | 15% | |
| Battery | Type | 36.8 Kw, Li-ion Batteries | |
| | Total voltage | 102 V | |
| | Charge time (h) | Trickle charge : 12h plug 16A 220V Fast charging : 6h plug 32A 220V (option) | |
| | Capacity | 360 Ah | |
| | Weight (kg) | 422 kg | |
| Tank | Volume of the tank (liter) | 1,500 Liters | |
| | Material | Stainless 304 L | |
| | Number of « anti-ballant ball » | 25 | |
| Water pump | Maximum rate | 80 L/mn | |
| | Capacity / Pressure | From 40 to 60 bars | |
| Washing ramp | Washing width (without side jet) | 1 500 mm | |
| | Number of positions | Multi-positions | |
| | Maximum / minimum height | 370 mm / 150 mm | |
| Washing perch (option) | Type of pistol | Variable and round jet | |
| | Length of the winder | 20 m | |
| | Scope | 160 ° | |

